

149987
10860****REVISED****
WATER WELL REPORT
STATE OF WASHINGTON

Start Card No.

W177613

. AKY 861

(1) OWNER: Name **PLATTER, DAVE/TR CAMANO** Address **PO BOX 673 STANWOOD, WA**(2) LOCATION OF WELL: County **ISLAND**

- NW 1/4 NE 1/4 Sec 28 T 32 N., R 3E WM

(2a) STREET ADDRESS OF WELL (or nearest address) **1172 SR 532**(3) PROPOSED USE: **DOMESTIC**

(10) WELL LOG

(4) TYPE OF WORK: Owner's Number of well
(If more than one)

Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change in formation.

NEW WELLMethod: **ROTARY**(5) DIMENSIONS: Diameter of well **6** inches
Drilled **173** ft. Depth of completed well **170** ft

MATERIAL

BROWN TOPSOIL

FROM

TO

BROWN CLAY**0****1****BROWN CLAY SILT & GRAVEL****1****9****BROWN GRAVEL SILT & SAND & GRAVEL****9****12****BROWN GRAVEL COMPACTED SILT & SAND****12****35****BROWN SILT SAND & GRAVEL****35****50****BROWN SAND GRAVEL & SILT****50****90****BROWN GRAVEL COARSE SAND****90****135****BROWN GRAVEL SAND & WATER****135****160****BROWN SAND GRAVEL & WATER****160****165****BROWN SAND SILT & GRAVEL & WOOD****165****170**

(Poorly permeable aquatard, hole stayed open, back filled 170'-173')

DEPT. OF ECOLOGY
FISCAL YEAR 2005
JUN 28 01:17Screens: **YES**

Manufacturer's Name

ALLOY MACHINEType **STAINLESS STEEL**

Model No.

Diam. **6** slot size **20** from **160** ft. to **165** ft.Diam. **6** slot size **15** from **165** ft. to **170** ft.Gravel packed: **NO**

Size of gravel

Gravel placed from ft. to ft.

Surface seal: **YES**To what depth? **18** ft.Material used in seal **BENTONITE**Did any strata contain unusable water? **NO**

Type of water? Depth of strata ft.

Method of sealing strata off

(7) PUMP: Manufacturer's Name

Type

H.P.

Well site meets all sighting criteria under I.C.C. 8.09 based on information supplied by the owner or owner's authorized representative.

(8) WATER LEVELS:

Land-surface elevation

above mean sea level ... ft.

Static level **141.2** ft. below top of well Date **05/13/04**

Artesian Pressure lbs. per square inch Date

Artesian water controlled by

Work started **04/29/04**Completed **04/30/04**

(9) WELL TESTS: Drawdown is amount water level is lowered below static level.

WELL CONSTRUCTOR CERTIFICATION:

I constructed and/or accept responsibility for construction of this well, and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.

Was a pump test made? **YES** If yes, by whom? **HAYES DRILLING**Yield: **28.5** gal./min with **1.5** ft. drawdown after **72** hrs.

Recovery data

Time Water Level Time Water Level Time Water Level

NAME **HAYES DRILLING, INC.**

(Person, firm, or corporation) (Type or print)

ADDRESS **5696 ERSKING RD. BOW, WA**[SIGNED] M. McAdam License No. **2566**

Contractor's

Registration No. **HAYESDI106J5**Date **05/25/04**

07777

149987

WATER WELL REPORT
STATE OF WASHINGTON

Start Card No

W177613

AKY 861

10860

(1) OWNER Name PLATTER, DAVE/TR CAMANO Address PO BOX 673 STANWOOD, WA		(10) WELL LOG																																					
(2) LOCATION OF WELL County ISLAND		- NW 1/4 NE 1/4 Sec 28 T 32 N , R 3E WM																																					
(2a) STREET ADDRESS OF WELL (or nearest address) 1172 SR 532																																							
(3) PROPOSED USE. DOMESTIC																																							
(4) TYPE OF WORK Owner's Number of well (If more than one) NEW WELL Method ROTARY		Formation Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change in formation																																					
(5) DIMENSIONS Diameter of well 6 inches Drilled 173 ft Depth of completed well 170 ft		<table border="1"><thead><tr><th>MATERIAL</th><th>FROM</th><th>TO</th></tr></thead><tbody><tr><td>BROWN TOPSOIL</td><td>0</td><td>1</td></tr><tr><td>BROWN CLAY</td><td>1</td><td>9</td></tr><tr><td>BROWN CLAY SILT & GRAVEL</td><td>9</td><td>12</td></tr><tr><td>BROWN GRAVEL SILT & SAND & GRAVEL</td><td>12</td><td>35</td></tr><tr><td>BROWN GRAVEL COMPACTED SILT & SAND</td><td>35</td><td>50</td></tr><tr><td>BROWN SILT SAND & GRAVEL</td><td>50</td><td>90</td></tr><tr><td>BROWN SAND GRAVEL & SILT</td><td>90</td><td>135</td></tr><tr><td>BROWN GRAVEL COARSE SAND</td><td>135</td><td>160</td></tr><tr><td>BROWN GRAVEL SAND & WATER</td><td>160</td><td>165</td></tr><tr><td>BROWN SAND GRAVEL & WATER</td><td>165</td><td>170</td></tr><tr><td>BROWN SAND SILT & GRAVEL & WOOD</td><td>170</td><td></td></tr></tbody></table>		MATERIAL	FROM	TO	BROWN TOPSOIL	0	1	BROWN CLAY	1	9	BROWN CLAY SILT & GRAVEL	9	12	BROWN GRAVEL SILT & SAND & GRAVEL	12	35	BROWN GRAVEL COMPACTED SILT & SAND	35	50	BROWN SILT SAND & GRAVEL	50	90	BROWN SAND GRAVEL & SILT	90	135	BROWN GRAVEL COARSE SAND	135	160	BROWN GRAVEL SAND & WATER	160	165	BROWN SAND GRAVEL & WATER	165	170	BROWN SAND SILT & GRAVEL & WOOD	170	
MATERIAL	FROM	TO																																					
BROWN TOPSOIL	0	1																																					
BROWN CLAY	1	9																																					
BROWN CLAY SILT & GRAVEL	9	12																																					
BROWN GRAVEL SILT & SAND & GRAVEL	12	35																																					
BROWN GRAVEL COMPACTED SILT & SAND	35	50																																					
BROWN SILT SAND & GRAVEL	50	90																																					
BROWN SAND GRAVEL & SILT	90	135																																					
BROWN GRAVEL COARSE SAND	135	160																																					
BROWN GRAVEL SAND & WATER	160	165																																					
BROWN SAND GRAVEL & WATER	165	170																																					
BROWN SAND SILT & GRAVEL & WOOD	170																																						
(6) CONSTRUCTION DETAILS Casing installed 6 " Dia from +3 ft to 160 ft WELDED " Dia. from ft to ft " Dia from ft to ft Perforations NO Type of perforator used SIZE of perforations in by in perforations from ft. to ft perforations from ft. to ft perforations from ft. to ft Screens YES Manufacturer's Name ALLOY MACHINE Type STAINLESS STEEL Model No. Diam 6 slot size 20 from 160 ft to 165 ft Diam 6 slot size 15 from 165 ft to 170 ft Gravel packed NO Size of gravel Gravel placed from ft to ft. Surface seal YES To what depth? 18 ft Material used in seal BENTONITE Did any strata contain unusable water? NO Type of water? Depth of strata ft Method of sealing strata off (Poorly permeable aquatard, hole stayed open, back filled 170"-173") JUN 01 2004 DEPARTMENT OF ECOLOGY WELL REGISTRATION																																							
(7) PUMP Manufacturer's Name Type H P		Well site meets all sighting criteria under I.C.C. 8.09 based on information supplied by the owner or owner's authorized representative.																																					
(8) WATER LEVELS Land-surface elevation above mean sea level ft. Static level 141.2 ft below top of well Date 05/13/04 Artesian Pressure lbs per square inch Date Artesian water controlled by		Work started 04/29/04 Completed 04/30/04																																					
(9) WELL TESTS Drawdown is amount water level is lowered below static level Was a pump test made? YES If yes, by whom? HAYES DRILLING Yield: 24 gal /min with 1.54 ft drawdown after 2.5 hrs Recovery data Time Water Level Time Water Level Time Water Level Date of test / / Bailer test 6 gal/min. 1 ft drawdown after .5 hrs Air test 15 gal/min w/ stem set at 155 ft for 1 hrs Artesian flow g p m. Date Temperature of water Was a chemical analysis made? NO		WELL CONSTRUCTOR CERTIFICATION I constructed and/or accept responsibility for construction of this well, and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief NAME HAYES DRILLING, INC. (Person, firm, or corporation) (Type or print) ADDRESS 5696 ERSHIG RD. BOW, WA [SIGNED] M. McAdam License No 2566 Contractor's Registration No HAYESDI106J5 Date 05/25/04																																					

07777